

New MA-206 / MA-212 / MA-224: 60W, 120W, 240W Mixer Amplifiers


Utilising efficient D-class amplifier technology, the latest generation of Inter-M's market-leading range of professional installation mixer amplifiers are smaller, lighter, more feature-full and have been stylishly remodelled for today's more demanding professional audio installation market.

With 5 selectable speaker outputs, 6 individually-controlled mic/line inputs, 5-band equaliser and numerous other features all as standard, the new MA-200 Series is ideal for user-manageable, zoned PA and background music in applications such as retail, education, corporate and church installations.

Features:

- 6 Mic/Line Inputs (3pin XLR / ¼" jack / dual phono)
- Priority Mute (Tel Input & Input 1)
- Link input (¼" jack)
- Amp In (¼" jack)
- Pre Amp Out (¼" jack)
- Chime/Siren
- External Mute (screw terminal)
- Remote Volume Control (screw terminal)
- Telephone In (screw terminal)
- Phantom Power (Inputs 1, 2 & 3)
- 'Active' LED display per input channel
- 5 Zone + All Loudspeaker Selector
- Optional 19" Rackmount Kit

• 19" Rack Mount Bracket Option: BKT-A120 Bracket



Specifications:

Model:	MA-206:	MA-212:	MA-224:
Output Power	60W RMS @ 100v / 4Ω	120W RMS @ 100v / 4Ω	240W RMS @ 100v / 4Ω
Inputs	3 x Mic/Line (3 pin XLR-F) 2 x Mic/Line (¼" jack) 1 x Line (dual phono) 1 x Telephone (screw terminal)		
Priority	1 = Tel Input, 2 = Mic 1		
Input Sensitivity/Impedance	Inputs: 1~5: Mic -50dBv/2KΩ, Line -10dBv/2KΩ Input 6: -10dBv/20KΩ Telephone: 0.775dBv/10KΩ		
Frequency Response (±3dB)	80Hz~15KHz		
Operating Temperature	-10°C ~ +40°C		
Power Requirement	230v AC, 50Hz		
Dimensions	420(W) x 88(H) x 328(D)mm		
Weight	5.4kg	6.7kg	8.0kg

